O.M.B. No 3067-0077 Expires May 31, 1993

ELEVATION CERTIFICATE FEDERAL EMERGENCY MANAGEMENT AGENCY NATIONAL FLOOD INSURANCE PROGRAM

elevation information necessary to ensure compliance with applicable community floodplain management ordinances, to the proper insurance premium rate, and/or to support a request for a Letter of Map Amendment or Revision (LOMA or LOMR). Instructions for completing this form can be found on the following pages.

SECTION A PROPERTY INFORMATION	FOR	NSURANCE COMPANY USE		
BUILDING OWNER'S NAME		Y NUMBER		
Walter D. Serwatka and Constance	eHolcomb			
STREET ADDRESS (Including Apt., Unit, Suite and/or Bldg. Number) OR P.O. ROUTE AND BOX NUMBER		ANY NAIC NUMBER		
<u>3555 Mistletoe Lane, Longboat K</u> OTHER DESCRIPTION (Lot and Block Numbers, etc.) Lot 63 Corey's Landing	ey, FL			
Longboat Key	STATE	ZIP CODE		
Longboat Key	Florida	34240		
SECTION B FLOOD INSURANCE RATE MAP (FIRM) INFORMATION				

Provide the following from the proper FIRM (See Instructions):

1. COMMUNITY NUMBER	2. PANEL NUMBER	3. SUFFIX	4. DATE OF FIRM INDEX	5. FIRM ZONE	6. BASE FLOOD ELEVATION (in AO Zones, use depth)
125126	0010	В	August 15, 1983	A-13	11.0'

7. Indicate the elevation datum system used on the FIRM for Base Flood Elevations (BFE): NGVD '29 Other (describe on back)
8. For Zones A or V, where no BFE is provided on the FIRM, and the community has established a BFE for this building site, indicate the community's BFE: https://www.elevation.com

SECTION C	BUILDING	ELEVATION	INFORMATION
-----------	----------	-----------	-------------

ng the Elevation Certificate Instructions, indicate the diagram number from the diagrams found on Pages 5 and 6 that best
ribes the subject building's reference level $\frac{6}{100}$. RM Zones A1-A30, AE, AH, and A (with BFE). The top of the reference level floor from the selected diagram is at an elevation
of 1 1 1.0 feet NGVD (or other FIRM datum-see Section B, Item 7).
(b). FIRM Zones V1-V30, VE, and V (with BFE). The bottom of the lowest horizontal structural member of the reference level from
the selected diagram, is at an elevation of feet NGVD (or other FIRM datum-see Section B, Item 7).
(c). FIRM Zone A (without BFE). The floor used as the reference level from the selected diagram is 🛄 . 🗋 feet above 🗌 or
below (check one) the highest grade adjacent to the building.
(d). FIRM Zone AO. The floor used as the reference level from the selected diagram is feet above or below (check one) the highest grade adjacent to the building. If no flood depth number is available, is the building's lowest floor (reference level) elevated in accordance with the community's floodplain management ordinance? Yes No Unknown
3. Indicate the elevation datum system used in determining the above reference level elevations: X NGVD '29 Other (describe under Comments on Page 2). (NOTE: If the elevation datum used in measuring the elevations is different than that used on the FIRM [see Section B, Item 7], then convert the elevations to the datum system used on the FIRM and show the conversion equation under Comments on Page 2.)
4. Elevation reference mark used appears on FIRM: 🗵 Yes 🗌 No (See Instructions on Page 4)
5. The reference level elevation is based on: X actual construction construction drawings (NOTE: Use of construction drawings is only valid if the building does not yet have the reference level floor in place, in which case this certificate will only be valid for the building during the course of construction. A post-construction Elevation Certificate will be required once construction is complete.)
6. The elevation of the lowest grade immediately adjacent to the building is: 7 .5 feet NGVD (or other FIRM datum-see Section B, Item 7).
SECTION D COMMUNITY INFORMATION
the community official responsible for verifying building elevations specifies that the reference level indicated in Section C, Item 1 not the "lowest floor" as defined in the community's floodplain management ordinance, the elevation of the building's "lowest

floor" as defined by the ordinance is: ______ feet NGVD (or other FIRM datum-see Section B, Item 7).

2. Date of the start of construction or substantial improvement

SECTION E CERTIFICATION

This certification is to be signed by a land surveyor, engineer, or architect who is authorized by state or local law to certify elevation information information for Zones A1–A30, AE, AH, A (with BFE),V1–V30,VE, and V (with BFE) is required. Community officials who are authorized by local law or ordinance to provide floodplain management information, may also sign to certification. In the case of Zones AO and A (without a FEMA or community issued BFE), a building official, a property owner, or a owner's representative may also sign the certification.


Reference level diagrams 6, 7 and 8 - Distinguishing Features–If the certifier is unable to certify to breakaway/non-breakaway wall, enclosure size, location of servicing equipment, area use, wall openings, or unfinished area Feature(s), then list the Feature(s) not included in the certification under Comments below. The diagram number, Section C, Item 1, must still be entered.

I certify that the information in Sections B and C on this certificate represents my best efforts to interpret the data available. I understand that any false statement may be punishable by fine or imprisonment under 18 U.S. Code, Section 1001.

CERTIFIER'S NAME	LICENSE NUMBER (or Affix Seal)		
Dennis R. Hoover	4419		
TITLE	COMPANY NAME		
Registered Land Surveyor	Bishop & Associat	tes	
ADDRESS	CITY	STATE ZIP	
78 Sarasota Center Blvd.	Sarasota	Florida 34240	
SIGNATURE Carming Horn	DATE	PHONE (813) 371-6362	

Copies should be made of this Certificate for: 1) community official, 2) insurance agent/company, and 3) building owner.





The diagrams above illustrate the points at which the elevations should be measured in A Zones and V Zones.

Elevations for all A Zones should be measured at the top of the reference level floor.

Elevations for all V Zones should be measured at the bottom of the lowest horizontal structural member.