ELEVATION CERTIFICATE FEDERAL EMERGENCY MANAGEMENT AGENCY NATIONAL FLOOD INSURANCE PROGRAM

U.M.B. No. 3067-0077 Expires July 31, 1999

ATTENTION: Use of this certificate does not provide a waiver of the flood insurance purchase requirement. This form is used only to prowide elevation information necessary to ensure compliance with applicable community floodplain management ordinances, to determine proper insurance premium rate, and/or to support a request for a Letter of Map Amendment or Revision (LOMA or LOMR). You are not equired to respond to this collection of information unless a valid OMB control number is displayed in the upper right corner of this form. Instructions for completing this form can be found on the following pages.

SECTION A PROPERTY INFORMATION					FOR INSURANCE COMPANY USE
BUILDING OWNER'S NAME EVA EBBESON & ARNE JOHANANSSON					POLICY NUMBER
STREET ADDRESS (Including Apt., Unit, Suite and/or Bldg. Number) OR P.O. ROUTE AND BOX NUMBER <u> 3621</u> <u> BAYOU</u> <u> CIRCLE</u> OTHER DESCRIPTION (Lot and Block Numbers, etc.)					COMPANY NAIC NUMBER
CITY SARASO	6	les U	NIT NO. 7 ONAT Key	PB.29, STATE	Pq 20 - 20A) ZIP CODE 3 4228
	SECTION B F	LOOD	ANCE RATE MAP (FIRM)	NFORMATION	15 2225
rovide the following from t	ne proper FIRM (See	Instructions):			10, 50
1. COMMUNITY NUMBER	2. PANEL NUMBER	3. SUFFIX ${\cal B}$	4. DATE OF FIRM INDEX MAY-18-92	5. FIRM ZONE A 13	6. BASE FLOOD ELEVATION (in AO Zones, use depth)
. For Zones A or V, where	no BFE is provided o	n the FIRM, ar	ase Flood Elevations (BFE nd the community has esta FIRM datum-see Section	blished a BFE t	Other (describe on back) Other (describe on back) for this building site, indicate
	SECTION	ON C BUILDI	NG ELEVATION INFORM	ATION	
Using the Elevation Certi ascribes the subject bu	ficate Instructions, in ilding's reference leve	dicate the diagr	ram number from the diagr	ams found on F	Pages 5 and 6 that best

27a). FIRM Zones A1-A30, AE, AH, and A (with BFE).	The top of the reference level floor from the selected diagram is at an elevation
of ノノゴ. Z feet NGVD (or other FIRM da	atum-see Section B, Item 7).

- (b). FIRM Zones V1-V30, VE, and V (with BFE). The bottom of the lowest horizontal structural member of the reference level from the selected diagram, is at an elevation of the selected diagram, is at an elevation of the selected diagram, is at an elevation of the selected diagram.
- (c). FIRM Zone A (without BFE). The floor used as the reference level from the selected diagram is Low feet above or below (check one) the highest grade adjacent to the building.
- (d). FIRM Zone AO. The floor used as the reference level from the selected diagram is _____. feet above ___ or below ___ (check one) the highest grade adjacent to the building. If no flood depth number is available, is the building's lowest floor (reference level) elevated in accordance with the community's floodplain management ordinance? 🗌 Yes 🗌 No 🗌 Unknown
- 3. Indicate the elevation datum system used in determining the above reference level elevations; 🗹 NGVD '29 🗌 Other (describe under Comments on Page 2). (NOTE: If the elevation datum used in measuring the elevations is different than that used on the FIRM [see Section B, Item 7], then convert the elevations to the datum system used on the FIRM and show the conversion equation under Comments on Page 2.)
- 4. Elevation reference mark used appears on FIRM: Ves Do (See Instructions on Page 4)
- 5. The reference level elevation is based on: 🗹 actual construction 🗌 construction drawings (NOTE: Use of construction drawings is only valid if the building does not yet have the reference level floor in place, in which case this certificate will only be valid for the building during the course of construction. A post-construction Elevation Certificate will be required once construction is complete.)
- 6. The elevation of the lowest grade immediately adjacent to the building is: 5.2 feet NGVD (or other FIRM datum-see Section B, Item 7).

SECTION D COMMUNITY INFORMATION

the community official responsible for verifying building elevations specifies that the reference level indicated in Section C, Item is not the "lowest floor" as defined in the community's floodplain management ordinance, the elevation of the building's "lowest	1
floor" as defined by the ordinance is: feet NGVD (or other FIRM datum-see Section B, Item 7). 2. Date of the start of construction or substantial improvement 7 - 8 - 9 6	

SECTION E CERTIFICATION

This certification is to be signed by a land surveyor, engineer, or architect who is authorized by state or local law to certify elevation information when the elevation information for Zones A1–A30, AE, AH, A (with BFE),V1–V30,VE, and V (with BFE) is required. Community officials who are authorized by local law or ordinance to provide floodplain management information, may also sign the certification. In the case of Zones AO and A (without a FEMA or community issued BFE), a building official, a property owner, or an owner's representative may also sign the certification.


Reference level diagrams 6, 7 and 8 - Distinguishing Features–If the certifier is unable to certify to breakaway/non-breakaway wall, enclosure size, location of servicing equipment, area use, wall openings, or unfinished area Feature(s), then list the Feature(s) not included in the certification under Comments below. The diagram number, Section C, Item 1, must still be entered.

I certify that the information in Sections B and C on this certificate represents my best efforts to interpret the data available. I understand that any false statement may be punishable by fine or imprisonment under 18 U.S. Code, Section 1001.

CERTIFIER'S NAME LICENSE NUMBER (or Affix Seal) URSIG 45 TITLE COMPANY NAME Profes ADDRESS CIT Pn SIGNATURE DATE PHONE n 79 2

Copies should be made of this Certificate for: 1) community official, 2) insurance agent/company, and 3) building owner.

5.66 COMMENTS: 46 -2 OULPS 2



The diagrams above illustrate the points at which the elevations should be measured in A Zones and V Zones.

Elevations for all A Zones should be measured at the top of the reference level floor.

Elevations for all V Zones should be measured at the bottom of the lowest horizontal structural member.