O M B: No 3067-0077 Expires May 31, 1993

ELEVATION CERTIFICATE. FEDERAL EMERGENCY MANAGEMENT AGENCY NATIONAL FLOOD INSURANCE PROGRAM

ATTENTION: Use of this certificate does not provide a waiver of the flood insurance purchase requirement. This form is used only to provide elevation information necessary to ensure compliance with applicable community floodplain management ordinances, to determine the proper insurance premium rate, and/or to support a request for a Letter of Map Amendment or Revision (LOMA or LOMR). Instructions for completing this form can be found on the following pages.

SECTION A PROPERTY INFORMATION	State and	FOR INSURANCE COMPANY USE
Building OWNER'S NAME Wedebrock Developments. LC		POLICY NUMBER
STREET ADDRESS (Including Apt.; Unit, Suite and or Bidg, Number) OR P.O. ROUTE AND BOX NUMBER	and a sub-	COMPANY NAIC NUMBER
4561 Gulf of Mexico Drive		
OTHER DESCRIPTION (Lot and Block Numbers, etc.)		
The Grande		

CITY

Longboat Key

ZIP CODE

STATE

F1

SECTION B FLOOD INSURANCE RATE MAP (FIRM) INFORMATION

Provide the following from the proper FIRM (See Instructions):

1. COMMUNITY NUMBER	2. PANEL NUMBER 3. SUFFIX		4 DATE OF FIRM INDEX	5. FIRM ZONE	6 BASE FLOOD ELEVATION
125126	0005	D	May 18, 1992	V17 & A13	(in AO Zones, use depth) 16'& 13'

7. Indicate the elevation datum system used on the FIRM for Base Flood Elevations (BFE): X NGVD '29 Other (describe on back) 8. For Zones A or V, where no BFE is provided on the FIRM, and the community has established a BFE for this building site, indicate the community's BFE: 11111 feet NGVD (or other FIRM datum-see Section B, Item 7).

SECTION C BUILDING ELEVATION INFORMATION

- 1. Using the Elevation Certificate Instructions, indicate the diagram number from the diagrams found on Pages 5 and 6 that best describes the subject building's reference level <u>6</u>.
- 2(a). FIRM Zones A1-A30, AE, AH, and A (with BFE). The top of the reference level floor from the selected diagram is at an elevation of [_____] feet NGVD (or other FIRM datum-see Section B, Item 7).
- (b). FIRM Zones V1-V30, VE, and V (with BFE). The bottom of the lowest horizontal structural member of the reference level from the selected diagram, is at an elevation of 11119191 feet NGVD (or other FIRM datum-see Section B, Item 7).
- (c). FIRM Zone A (without BFE). The floor used as the reference level from the selected diagram is []]. feet above or below (check one) the highest grade adjacent to the building.
- (d). FIRM Zone AO. The floor used as the reference level from the selected diagram is ______ feet above _____ or below _____ (check one) the highest grade adjacent to the building. If no flood depth number is available, is the building's lowest floor (reference level) elevated in accordance with the community's floodplain management ordinance? [______ Yes ____ No _____ Unknown
- 3. Indicate the elevation datum system used in determining the above reference level elevations: NGVD '29 Other (describe under Comments on Page 2). (NOTE: If the elevation datum used in measuring the elevations is different than that used on the FIRM [see Section B, Item 7], then convert the elevations to the datum system used on the FIRM and show the conversion equation under Comments on Page 2.)
- 4. Elevation reference mark used appears on FIRM: Yes X No (See Instructions on Page 4)
- 5. The reference level elevation is based on: 🖾 actual construction 🗋 construction drawings (NOTE: Use of construction drawings is only valid if the building does not yet have the reference level floor in place, in which case this certificate will only be valid for the building during the course of construction. A post-construction Elevation Certificate will be required once construction is complete.)
- 6. The elevation of the lowest grade immediately adjacent to the building is: 1 1 1 181. 41 feet NGVD (or other FIRM datum-see Section B, Item 7).

SECTION D COMMUNITY INFORMATION

1.	If the community official responsible for verifying building playations an artification in the
	is not the "lowest floor" as defined in the community's floodoloin measurements that the reference level indicated in Section C, ftem 1
	floor" as defined by the ordinance in the commonly's hooppain management ordinance, the elevation of the building's "lowest
2.	Date of the start of construction B, Item 7).
	and on the start of construction or substantial improvement

		Alt and the second	•	
	والمواد المريح والمريح	Katala	•	
	SECTION E CERT	IFICATION		

This certification is to be signed by a land surveyor, engineer, or architect who is authorized by state or local law to certify elevation information when the elevation information for Zones A1–A30, AE, AH, A (with BFE),V1–V30,VE, and V (with BFE) is required. Community officials who are authorized by local law or ordinance to provide floodplain management information, may also sign the certification. In the case of Zones AO and A (without a FEMA or community issued BFE), a building official, a property owner, or an owner's representative may also sign the certification.

Reference level diagrams 6, 7 and 8 - Distinguishing Features-If the certifier is unable to certify to breakaway/non-breakaway wall, enclosure size, location of servicing equipment, area use, wall openings, or unfinished area Feature(s), then list the Feature(s) not included in the certification under Comments below. The diagram number, Section C, Item 1, must still be entered.

I certify that the information in Sections B and C on this certificate represents my best efforts to interpret the data available. I understand that any false statement may be punishable by fine or imprisonment under 18 U.S. Code, Section 1001.

CERTIFIER'S NAME	LICENSE NUMBER (or Affix Seal) R.L.S. #4554 COMPANY NAME			
William R.Knight, Jr.				
ADDRESS	B & C Surveying	. STATE Fl	ZIP 34233	
SIGNATURE	12/16/97	PHONE 941-92	21-4297	
Copies should be made of this Certificate for: 1) of	community official, 2) Insurance agent/c	ompany, and 3) buildi	ing owner.	
The for the second seco				
,			•	
5				



The diagrams above illustrate the points at which the elevations should be measured in A Zones and V Zones.

ł

Elevations for all A Zones should be measured at the top of the reference level floor.

Elevations for all V Zones should be measured at the bottom of the lowest horizontal structural member.