## **ELEVATION CERTIFICATE**

## FEDERAL EMERGENCY MANAGEMENT AGENCY NATIONAL FLOOD INSURANCE PROGRAM

N: Use of this certificate does not provide a waiver of the flood insurance purch evation information necessary to ensure compliance with applicable community letermine the proper insurance premium rate, and/or to support a request for a Letter of N instructions for completing this form can be found on the	lloodplain managen lap Amendment or	nent ordinances, to Revision (LOMA of LOMR).
SECTION A PROPERTY INFORMATION		INSURANCE COMPANY USE
BUILDING OWNER'S NAME ( )		POLICY NUMBER
STREET ADDRESS (Including Apt., Unit, Suite and/or Bidg, Number) OR P.O. ROUTE AND BOX NUMBER  531 HARBOR GATE WAY		APANY NAIC NUMBER
OTHER DESCRIPTION (Lot and Block Numbers, etc.)		
COT. 4. DAY ISCES UNIT!	STATE PL,	ZIP CODE 34228
SECTION B FLOOD INSURANCE RATE MAP (FIRM)	NFORMATION	
rovide the following from the proper FIRM (See Instructions):	te.	
1, COMMUNITY NUMBER 2. PANEL NUMBER 3. SUFFIX 4. DATE OF FIRM INDEX 125124 OULD B 5/18/97	5. FIRM ZONE	e BASE FLOOD ELEVATION (In AO Zenes, use depth)
Indicate the elevation datum system used on the FIRM for Base Flood Elevations (BFE). For Zones A or V, where no BFE is provided on the FIRM, and the community has estate the community's BFE:	District a Di E for ti	Other (describe on back) his building site, indicate
SECTION C BUILDING ELEVATION INFORM	ATION	
2(a). FIRM Zones A1-A30, AE, AH, and A (with BFE). The top of the reference level floor of 102 13 feet NGVD (or other FIRM datum-see Section B, Item 7).  (b). FIRM Zones V1-V30, VE, and V (with BFE). The bottom of the lowest horizontal strength the selected diagram, is at an elevation of 102 103 feet NGVD (or other FIRM Co.). FIRM Zone A (without BFE). The floor used as the reference level from the selected below 102 (check one) the highest grade adjacent to the building.  (d). FIRM Zone AO. The floor used as the reference level from the selected diagram is one) the highest grade adjacent to the building. If no flood depth number is available to the building in the highest grade adjacent to the building.	uctural member of to diagram is d	the reference level from on B, Item 7).  Let feet above or or or below (check owest floor (reference
level) elevated in accordance with the community's floodplain management ordinance.  3. Indicate the elevation datum system used in determining the above reference level elevation Comments on Page 2). (NOTE: If the elevation datum used in measuring the elevation datum used in measuring the elevation used in measuring the elevation used in measuring the elevation under Comments on Page 2.)  4. Elevation reference mark used appears on FIRM:   Yes No (See Instructions of	vations (X) NGVD elevations is different sed on the FIRM an	it than that used on
5. The reference level elevation is based on: actual construction Construction d		
(NOTE: Use of construction drawings is only valid if the building does not yet have the case this certificate will only be valid for the building during the course of construction.  will be required once construction is complete.)  6. The elevation of the lowest grade immediately adjacent to the building is:	e reference level 110 A post-construction	II Elevation Certificate
Section B, Item 7).		
SECTION D COMMUNITY INFORMATION		
community official responsible for verifying building elevations specifies that the is not the "lowest floor" as defined in the community's floodplain management ordinan floor" as defined by the ordinance is:	ce, the elevation of	the building's lowest

## SECTION E CERTIFICATION

This certification is to be signed by a land surveyor, engineer, or architect who is authorized by state or local law to certify elev information when the elevation information for Zones A1–A30, AE, AH, A (with BFE), V1–V30, VE, and V (with BFE) is required. Community officials who are authorized by local law or ordinance to provide floodplain management information, may also sign certification. In the case of Zones AO and A (without a FEMA or community issued BFE), a building official, a property owner, or an owner's representative may also sign the certification.

Reference level diagrams 6, 7 and 8 - Distinguishing Features—If the certifler is unable to certify to breakaway/non-breakaway wall, enclosure size, location of servicing equipment, area use, wall openings, or unfinished area Feature(s), then list the Feature(s) not, included in the certification under Comments below. The diagram number, Section C, Item 1, must still be entered.

I certify that the information in Sections B and C on this certificate represents my best efforts to interpret the data available. I understand that any false statement may be punishable by fine or imprisonment under 18 U.S. Code, Section 1001.

CERTIFIER'S NAME LICENSE NUMBER (or Affix Seal) PLS 3868 Lawrence R Weber President CWENE PAMEngineering & Surveying, ADDRESS 34231 CITY STATE Swift Road 3932 Suilte Sarasota F1 SIGNATURE PHONE 941/921-3914 Copies should be made of this Certificate for: 1) community official, 2) insurance agent/company, and 3) building owner.

COMMENTS:

ON PILES WITH ON PIERS, OR COLUMNS SLAB BASEMENT ZONES ZONES ZONES ZONES ZONES REFERENCE REFERENCE LEVEL REFERENCE BASE LEVEL ELEVATION ADJACENT

The diagrams above illustrate the points at which the elevations should be measured in A Zones and V Zones.

Elevations for all A Zones should be measured at the top of the reference level floor.

Elevations for all V Zones should be measured at the bottom of the lowest horizontal structural member.