ELEVATION CERTIFICATE FEDERAL EMERGENCY MANAGEMENT AGENCY NATIONAL FLOOD INSURANCE PROGRAM O.M.B. NO. 3067-0077 Expires May 31, 1996

BP.10968

ATTENTION: Use of this certificate does not provide a waiver of the flood insurance purchase requirement. This form is used only to provide elevation information necessary to ensure compliance with applicable community floodplain management ordinances, to determine the proper insurance premium rate, and/or to support a request for a Letter of Map Amendment or Revision (LOMA or LOMR). Instructions for completing this form can be found on the following pages.

SECTION A PROPERTY INFORMATION	FOR INSURANCE COMPANY USE
BUILDING OWNER'S NAME Susan Lewis - Abrahamson	POLICY NUMBER
STREET ADDRESS (Including Apt., Unit, Suite and/or Bldg. Number) OR P.O. ROUTE AND BOX NUMBER 5345 Gulf of Mexico Drive	COMPANY NAIC NUMBER

OTHER DESCRIPTION (Lot and Block Numbers, etc.)

Longboat Key				state Florida	ZIP CODE 34228
SECTION B FLOOD INSURANCE RATE MAP (FIRM) INFORMATION					
Provide the following from the	he proper FIRM (See	Instructions):			
1. COMMUNITY NUMBER	2. PANEL NUMBER	3. SUFFIX	4. DATE OF FIRM INDEX	5. FIRM ZONE	6. BASE FLOOD ELEVATION (in AO Zones, use depth)
125126	0005	D	May 18, 1992	A 13	<u> </u>

7. Indicate the elevation datum system used on the FIRM for Base Flood Elevations (BFE): X NGVD '29 Other (describe on back)
8. For Zones A or V, where no BFE is provided on the FIRM, and the community has established a BFE for this building site, indicate the community's BFE:
I feet NGVD (or other FIRM datum-see Section B, Item 7)

SECTION C BUILDING ELEVATION INFORMATION

1	. Using the Elevation Certificate Instructions, indicate the diagram number from the diagrams found on Pages 5 and 6 that best
_	describes the subject building's reference level 8
2	(a). FIRM Zones A1-A30, AE, AH, and A (with BFE). The top of the reference level floor from the selected diagram is at an elevation
	of 1 8 .1 feet NGVD (or other FIRM datum-see Section B, Item 7).
	(b). FIRM Zones V1-V30, VE, and V (with BFE). The bottom of the lowest horizontal structural member of the reference level from
	the selected diagram, is at an elevation of LLLL feet NGVD (or other FIRM datum-see Section B, Item 7).
	(c). FIRM Zone A (without BFE). The floor used as the reference level from the selected diagram is LLL. feet above D or
	below (check one) the highest grade adjacent to the building.
	(d). FIRM Zone AO. The floor used as the reference level from the selected diagram is feet above or below (check
	one) the highest grade adjacent to the building. If no flood depth number is available, is the building's lowest floor (reference
	level) elevated in accordance with the community's floodplain management ordinance? 🗌 Yes 🗌 No 🗌 Unknown
3	Indicate the elevation datum system used in determining the above reference level elevations: X NGVD '29 🗌 Other (describe
	under Comments on Page 2). (NOTE: If the elevation datum used in measuring the elevations is unterent than that used on
	the FIRM [see Section B, Item 7], then convert the elevations to the datum system used on the FIRM and show the conversion
	equation under Comments on Page 2.)
4	. Elevation reference mark used appears on FIRM: 🛛 Yes 🗌 No (See Instructions on Page 4)
5	5. The reference level elevation is based on: 🛛 actual construction 🗌 construction drawings
	(NOTE: Use of construction drawings is only valid if the building does not yet have the reference level floor in place, in which
	case this certificate will only be valid for the building during the course of construction. A post-construction Elevation Certificate

will be required once construction is complete.)
6. The elevation of the lowest grade immediately adjacent to the building is: building is: www.see.com is: www.see is: www.see is: www.see is: www.see.com is: www.see.com is: <a href="https://www.s

SECTION D COMMUNITY INFORMATION

	If the community official responsible for verifying building elevations specifies that the reference level indicated in Section C, Item 1 is not the "lowest floor" as defined in the community's floodplain management ordinance, the elevation of the building's "lowest floor" as defined by the ordinance is:
2.	Date of the start of construction or substantial improvement


SECTION E CERTIFICATION

This certification is to be signed by a land surveyor, engineer, or architect who is authorized by state or local law to certify elevation information when the elevation information for Zones A1–A30, AE, AH, A (with BFE),V1–V30,VE, and V (with BFE) is required. Community officials who are authorized by local law or ordinance to provide floodplain management information, may also sign the certification. In the case of Zones AO and A (without a FEMA or community issued BFE), a building official, a property owner, or an owner's representative may also sign the certification.

Reference level diagrams 6, 7 and 8 - Distinguishing Features-If the certifier is unable to certify to breakaway/non-breakaway wall, enclosure size, location of servicing equipment, area use, wall openings, or unfinished area Feature(s), then list the Feature(s) not included in the certification under Comments below. The diagram number, Section C, Item 1, must still be entered.

I certify that the information in Sections B and C on this certificate represents my best efforts to interpret the data available. I understand that any false statement may be punishable by fine or imprisonment under 18 U.S. Code, Section 1001.

Mark E. Bassett	#4394				
CERTIFIER'S NAME	LICENSE	NUMBER (or Affix Sea	l)		
Registered Land Surveyor	Bishop & Associates				
TITLE	COMPANY NAME				
78 Sarasota Center Blvd.	Sarasota	FL		34240	
ADDRESS 4. 7. 9.	CITY		STATE	ZIP	
	1		371-6362		
SIGNATURE Mark & Basser	4	DATE	PHONE		
Copies should be made of this Certificate for: 1) community official, 2) insu	urance agent/con	pany, and 3) building	owner.	
COMMENTS: House nearest to Gult	f of Mexico Drive				



Elevations for all A Zones should be measured at the top of the reference level floor.

Elevations for all V Zones should be measured at the bottom of the lowest horizontal structural member.