ELEVATION CERTIFICATE

FEDERAL EMERGENCY MANAGEMENT AGENCY NATIONAL FLOOD INSURANCE PROGRAM

ATTENTION: Use of this certificate does not provide a waiver of the flood insurance purchase requirement. This form is used only to provide elevation information necessary to ensure compliance with applicable community floodplain management ordinances, to determine the proper insurance premium rate, and/or to support a request for a Letter of Map Amendment or Revision (LOMA or LOMR).

Instructions for completing this form can be found on the following pages.

SECTION A PROPERTY INFORMATION -	FOR INSURANCE COMPANY USE
BUILDING OWNER'S NAME	POLICY NUMBER
Edwin Molyneux Webb STREET ADDRESS (Including Apt., Umt. Suite and/or Bldg. Number) OR P.O. ROUTE AND BOX NUMBER 626 Nacton St.	COMPANY NAIC NUMBER
OTHER DESCRIPTION (Lot and Block Numbers, etc.) VOT 59 SUEEPY VAM O	1.1.1
Longboat Key FL SECTION B FLOOD INSURANCE RATE MAP (FIRM) INFORMATION	34228 1
Provide the following from the proper FIRM (See Instructions):	
1. COMMUNITY NUMBER 2. PANEL NUMBER 3. SUFFIX 4. DATE OF FIRM INDEX 5. FIRM ZONE 125126 0005 D 18 May 92 A-13	6. BASE FLOOD ELEVATION (in AO Zones, use depth)
7. Indicate the elevation datum system used on the FIRM for Base Flood Elevations (BFE): NGVD '29 8. For Zones A or V, where no BFE is provided on the FIRM, and the community has established a BFE the community's BFE:	Other (describe on back) for this building site, indicate
SECTION C BUILDING ELEVATION INFORMATION	
describes the subject building's reference level 2(a). FIRM Zones A1-A30, AE, AH, and A (with BFE). The top of the reference level floor from the select of feet NGVD (or other FIRM datum—see Section B, Item 7). (b). FIRM Zones V1-V30, VE, and V (with BFE). The bottom of the lowest horizontal structural member the selected diagram, is at an elevation of feet NGVD (or other FIRM datum—see Section B, Item 7). (c). FIRM Zone A (without BFE). The floor used as the reference level from the selected diagram is below (check one) the highest grade adjacent to the building. (d). FIRM Zone AO. The floor used as the reference level from the selected diagram is feet a one) the highest grade adjacent to the building. If no flood depth number is available, is the building level) elevated in accordance with the community's floodplain management ordinance? Yes funder Comments on Page 2). (NOTE: If the elevation datum used in measuring the elevations is difficult the FIRM [see Section B, Item 7], then convert the elevations to the datum system used on the FIRM equation under Comments on Page 2.) 4. Elevation reference mark used appears on FIRM: Yes, No (See Instructions on Page 4) 5. The reference level elevation is based on actual construction construction drawings (NOTE: Use of construction drawings is only valid if the building does not yet have the reference leve case this certificate will only be valid for the building during the course of construction. A post-construction will be required once construction is complete.) 6. The elevation of the lowest grade immediately adjacent to the building is:	r of the reference level from Section B, Item 7). feet above or pelow (check g's lowest floor (reference) No Unknown VD '29 Other (describe erent than that used on and show the conversion
SECTION D COMMUNITY INFORMATION	
1. If the community official responsible for verifying building elevations specifies that the reference level is not the "lowest floor" as defined in the community's floodplain management ordinance, the elevation floor" as defined by the ordinance is:	of the building's "lowest


SECTION E CERTIFICATION

This certification is to be signed by a land surveyor, engineer, or architect who is authorized by state or local law to certify elevation information when the elevation information for Zones A1–A30, AE, AH, A (with BFE),V1–V30,VE, and V (with BFE) is required. Community officials who are authorized by local law or ordinance to provide floodplain management information, may also sign the certification. In the case of Zones AO and A (without a FEMA or community issued BFE), a building official, a property owner, or an owner's representative may also sign the certification.

Reference level diagrams 6, 7 and 8 - Distinguishing Features-If the certifier is unable to certify to breakaway/non-breakaway wall, enclosure size, location of servicing equipment, area use, wall openings, or unfinished area Feature(s), then list the Feature(s) not included in the certification under Comments below. The diagram number, Section C, Item 1, must still be entered.

I certify that the information in Sections B and C on this certificate represents my best efforts to interpret the data available. I understand that any false statement may be punishable by fine or imprisonment under 18 U.S. Code, Section 1001.

CERTIFIER'S NAME LUG MBERN	LICENSE NUMBER (or Affix Seal) 5. 4 3599
TITLE SUPVOYOR	COMPANY NAME AUBERTY of MSOL. P.A.
ADDRESS 1599 KPEX POMO	CITY SAPPLYOTA KISTATE 347 AC
SIGNATURE AND	16 MAPE 93 PHONE 378-5667
Copies should be made of this Certificate for: 1)	community official, 2) insurance agent/company, and 3) building owner.
	community official, 2) insurance agent/company, and 3) building owner.
Copies should be made of this Certificate for: 1)	community official, 2) insurance agent/company, and 3) building owner.
	community official, 2) insurance agent/company, and 3) building owner.
	community official, 2) insurance agent/company, and 3) building owner.



The diagrams above illustrate the points at which the elevations should be measured in A Zones and V Zones.

Elevations for all A Zones should be measured at the top of the reference level floor.

Elevations for all V Zones should be measured at the bottom of the lowest horizontal structural member.