ELEVATION CERTIFICATE

FEDERAL EMERGENCY MANAGEMENT AGENCY NATIONAL FLOOD INSURANCE PROGRAM

TION: Use of this certificate does not provide a waiver of the flood insurance purchase requirement. This form is used only to elevation information necessary to ensure compliance with applicable community floodplain management ordinances, to determine the proper insurance premium rate, and/or to support a request for a Letter of Map Amendment or Revision (LOMA or LOMR). Instructions for completing this form can be found on the following pages.

SECTION A PROPERTY INFORMATION					FOR INSURANCE COMPANY USE
BUILDING OWNER'S NAME					POLICY NUMBER
Edward and Patricia Kertz					
STREET ADDRESS (Including Apt., Unit, Suite and/or Bldg. Number) OR P.O. ROUTE AND BOX NUMBER 716 Hideaway Bay Lane					COMPANY NAIC NUMBER
OTHER DESCRIPTION (Lot and I		0.000	<u>- 10, 31, 210, 216, 216</u> 		
		vision.	Manatee County	. FL	
CITY	-11			STATE	ZIP CODE
Longboat Key	·	alay ké si Pengak Ké		FL	34228
	SECTION B FL	OOD INSURA	NCE RATE MAP (FIRM)	INFORMATION	1
^o rovide the following from the	ne proper FIRM (See	nstructions):	local i dya 1 -		1 (D. W.)
1. COMMUNITY NUMBER	2. PANEL NUMBER	3. SUFFIX	4. DATE OF FIRM INDEX	5. FIRM ZONE	6. BASE FLOOD ELEVATION .
125126	0005	D	May 18, 1992	A13	(in AO Zones, use depth) 10
3. For Zones A or V, where	no BFE is provided or	the FIRM, an	ase Flood Elevations (BFE of the community has esta FIRM datum-see Section	blished a BFE f	Other (describe on back) for this building site, indicate
1.	SECTIO	NC BUILDI	NG ELEVATION INFORM	ATION	10 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0
 ibes the subject build is the subject buil	ilding's reference level AE, AH, and A (with Bi t NGVD (or other FIRI /E, and V (with BFE). s at an elevation of BFE). The floor used the highest grade adj oor used as the refere adjacent to the buildir dance with the commu-	FE). The top FE). The top datum-see The bottom c as the referen acent to the bi- ence level from ng. If no flood unity's floodpla termining the	Section B, Item 7). of the lowest horizontal stru- feet NGVD (or other FIRI- nce level from the selected uilding. In the selected diagram is depth number is available ain management ordinance above reference level elever	from the select uctural member d datum-see S diagram is 	ted diagram is at an elevation of the reference level from ection B, Item 7).
equation under Comment	s, item 7], then conven s on Page 2.)	t the elevation	is to the datum system use	ed on the FIRM	and show the conversion
4. Elevation reference mark used appears on FIRM: 🗌 Yes 🗵 No (See Instructions on Page 4)					
5. The reference level elevat (NOTE: Use of constructi case this certificate will on will be required once const	on drawings is only va ly be valid for the build truction is complete.)	alid if the build ling during the	ing does not yet have the course of construction. A	reference level post-construct	tion Elevation Certinoa e
5. The elevation of the lowest grade immediately adjacent to the building is: 5.2' feet NGVD (or other FIRM datasee					
	SEC	TION D CO	MMUNITY INFORMATION	1	62
	sponsible for verifying	building eleva	ations specifies that the re	ference level in	dicated in Section C. Item 1

is not the "lowest floor" as defined in the community's floodplain management ordinance, the elevation of the building's "lowest floor" as defined by the ordinance is:

. Date of the start of construction or substantial improvement

NT # BP. 11196

SECTION E CERTIFICATION

This certification is to be signed by a land surveyor, engineer, or architect who is authorized by state or local law to certify elevation information when the elevation information for Zones A1–A30, AE, AH, A (with BFE),V1–V30,VE, and V (with BFE) is required. Community officials who are authorized by local law or ordinance to provide floodplain management information, may also sign the certification. In the case of Zones AO and A (without a FEMA or community issued BFE), a building official, a property owner, or an owner's representative may also sign the certification.

Reference level diagrams 6, 7 and 8 - Distinguishing Features–If the certifier is unable to certify to breakaway/non-breakaway wall, enclosure size, location of servicing equipment, area use, wall openings, or unfinished area Feature(s), then list the Feature(s) not included in the certification under Comments below. The diagram number, Section C, Item 1, must still be entered.

I certify that the information in Sections B and C on this certificate represents my best efforts to interpret the data available. I understand that any false statement may be punishable by fine or imprisonment under 18 U.S. Code, Section 1001.

CERTIFIER'S NAME LICENSE NUMBER (or Affix Seal) Ralph J. Rhodes Florida P.L.S. #3959 COMPANY NAME TITLE Ralph J. Rhodes Owner ADDRESS CITY STATE ZIP 2201 Cantu Court) - Ste. 200 FL 34232. Sarasota SIGNATURE DATE (813) 379-2403 1/5/94 Copies should be made of this Certificate for: 1) community official, 2) insurance agent/company, and 3) building owner. COMMENTS: Elevation benchmark used was D.N.R. 13-84-B10 disk in sidewalk, 1929 datum. Garage floor elevation = 7.9 but has flow-through 15550 6 openings for hydrostatic relief. noissidents. The constant mappingien ON PILES, WITH ON BASEMENT PIERS, OR COLUMNS SLAB V V ZONES ZONES ZONES ZONES ZONES REFERENCE LEVE REFERENCE BASE REFERENCE LEVEL LEVEL FLOOD ELEVATION BASE FLOOD REFERENCE ADJACENT LEVEL GRADE REFERENCE ADJACENT LEVEL ADJACENT GRADE The diagrams above illustrate the points at which the elevations should be measured in A Zones and V Zones. Elevations for all A Zones should be measured at the top of the reference level floor. Elevations for all V Zones should be measured at the bottom of the lowest horizontal structural member.