ELEVATION CERTIFICATE FEDERAL EMERGENCY MANAGEMENT AGENCY

O.M.B. No 3067-007 Expires May 31, 1993

NATIONAL FLOOD INSURANCE PROGRAM

ATTENTION: Use of this certificate does not provide a waiver of the flood insurance purchase requirement. This form is used only to provide elevation information necessary to ensure compliance with applicable community floodplain management ordinances, to determine the proper insurance premium rate, and/or to support a request for a Letter of Map Amendment or Revision (LOMA or LOMR). Instructions for completing this form can be found on the following pages.

SECTION A	PROPERTY INFORMATION	a sian signatisi a bian Sa sian si malangan	FOR INSURANCE COMPANY USE
BUILDING OWNER'S NAME	L P STA STATES	a zasta a secular	POLICY NUMBER
HUNT BUILDING, CORP.			
STREET ADDRESS (Including Apt., Unit, Suite and/or E	ldg. Number) OR P.O. ROUTE AND BOX NU	MBER	COMPANY NAIC NUMBER
828-830 Evergreen Pl			
OTHER DESCRIPTION (Lot and Block Numbers, etc.)			
BUILDING 39, CEDARS EAST, SE	CTION III	and the stagilite over expansion in the second second	
CITY	74 ° 5	STATE	ZIP COD5

LONGBOAT KEY

SECTION B FLOOD INSURANCE RATE MAP (FIRM) INFORMATION

FL

Provide the following from the proper FIRM (See Instructions):

1. COMMUNITY NUMBER	2. PANEL NUMBER	3. SUFFIX	4. DATE OF FIRM INDEX	5. FIRM ZONE	6. EASE FLOOD ELEVATION (in AO Zones, use depth)
125126	0005	С	10/01/83	A 13	= 10

7. Indicate the elevation datum system used on the FIRM for Base Flood Elevations (BFE): KINGVD '29 Other (describe on back) 8. For Zones A or V, where no BFE is provided on the FIRM, and the community has established a BFE for this building site, indicate the community's BFE:

SECTION C BUILDING ELEVATION INFORMATION

1. Using the Elevation Certificate Instructions, indicate the diagram number from the diagrams found on Pages 5 and 6 that best describes the subject building's reference level $\frac{8}{2}$.
2(a). FIRM Zones A1-A30, AE, AH, and A (with BFE). The top of the reference level floor from the selected diagram is at an elevation
of 16.9 feet NGVD (or other FIRM datum-see Section B, Item 7).
(b). FIRM Zones V1-V30, VE, and V (with BFE). The bottom of the lowest horizontal structural member of the reference level from
the selected diagram, is at an elevation of feet NGVD (or other FIRM datum-see Section B, Item 7).
(c). FIRM Zone A (without BFE). The floor used as the reference level from the selected diagram is feet above or
below (check one) the highest grade adjacent to the building.
(d). FIRM Zone AO. The floor used as the reference level from the selected diagram is feet above or below (chec one) the highest grade adjacent to the building. If no flood depth number is available, is the building's lowest floor (reference level) elevated in accordance with the community's floodplain management ordinance? Yes No Unknown
3. Indicate the elevation datum system used in determining the above reference level elevations: 🖾 NGVD '29 🗌 Other (describe under Comments on Page 2). (NOTE: If the elevation datum used in measuring the elevations is different than that used on the FIRM [see Section B, Item 7], then convert the elevations to the datum system used on the FIRM and show the conversion equation under Comments on Page 2.)
4. Elevation reference mark used appears on FIRM: Ves X No (See Instructions on Page 4)
5. The reference level elevation is based on: 🖾 actual construction 🗌 construction drawings (NOTE: Use of construction drawings is only valid if the building does not yet have the reference level floor in place, in which case this certificate will only be valid for the building during the course of construction. A post-construction Elevation Certificate will be required once construction is complete.)
6. The elevation of the lowest grade immediately adjacent to the building is: 16.8 feet NGVD (or other FIRM datum see Section B, Item 7).
SECTION D COMMUNITY INFORMATION
. If the community official responsible for verifying building elevations specifies that the reference level indicated in Section C Item
is not the "lowest floor" as defined in the community's floodplain management ordinance, the elevation of the building's "lowest

floor" as defined by the ordinance is:

2. Date of the start of construction or substantial improvement

SECTION E CERTIFICATION

This certification is to be signed by a land surveyor, engineer, or architect who is authorized by state or local law to certify elevation information when the elevation information for Zones A1–A30, AE, AH, A (with BFE),V1–V30,VE, and V (with BFE) is required. Community officials who are authorized by local law or ordinance to provide floodplain management information, may also sign the certification. In the case of Zones AO and A (without a FEMA or community issued BFE), a building official, a property owner, or an owner's representative may also sign the certification.

Reference level diagrams 6, 7 and 8 - Distinguishing Features–If the certifier is unable to certify to breakaway/non-breakaway wall, enclosure size, location of servicing equipment, area use, wall openings, or unfinished area Feature(s), then list the Feature(s) not included in the certification under Comments below. The diagram number, Section C, Item 1, must still be entered.

I certify that the information in Sections B and C on this certificate represents my best efforts to interpret the data available I understand that any false statement may be punishable by fine or imprisonment under 18 U.S. Code, Section 1001.

ERTIFIER'S NAME	LICE	NSE NUMBER (or Affix S	eal)	
JAMES N. GATCH JR		4295		1
ITLE ASSISTANT DIRECTOR OF SURVEY	TNG ZOLLER NALL	AR & SHROYER,	TNC	
DDRESS ASSISTENT DIRECTOR OF SORVER	CITY	AR & DIROTLR,	STATE	710
P.O. BOX 9448	BRADENTON		FL	ZIP 34206
IGNATORE Sal Gatel J		DATE 2/22/91	PHONE 813-784-8080	
Copies should be made of this Certificate	e for: 1) community official, 2)			
COMMENTS:	an an tha the group of the second	1-1., NA) -	Tel on memory ver	Far Zones A
annun minim	1998 Alexandra 1997 - 1998 Alexandra de la composición de la compo	8 - 8		PD7885C5 903
and the second statement of the second se			na a second total a second	i in the second second
			far an	alargenta e Per
and the second			A A A A A A A A A A A A A A A A A A A	THE PARTY OF
(2) The second s second second sec			NOH MILLER	
ter 4 militaria da managaria da managaria. Secolo da militaria da managaria da managaria.			2 (20) (20) (20) (20) (20) (20) (20) (20	10 10 10
teres somerator of the second sound in the second sound sound in t			1 (* 5 5 5 5 * 5 * 5 * 5 * 5 * 5 * 5 * 5	10 10 10 10 10 10 10 10 10 10 10 10 10 1
ON			ON PILES,	in an
	WITH BASEMENT		ON PILES, PIERS, OR COLUMNS	
ON SLAB A V	BASEMENT		PIERS, OR COLUMNS	
ON SLAB	BASEMENT	REFERENC	PIERS, OR COLUMNS	
ON SLAB A V ZONES ZONES	A ZONES	BASE	PIERS, OR COLUMNS	REFERENCE
ON SLAB A V ZONES ZONES	A ZONES -	I EVEI	PIERS, OR COLUMNS	
ON SLAB A V ZONES ZONES	A ZONES -	BASE LEVEL	PIERS, OR COLUMNS	
ON SLAB A V ZONES ZONES	BASEMENT ZONES	BASE LOOD EVATION	PIERS, OR COLUMNS	
ON SLAB ZONES ZONES REFERENCE LEVEL BASE FLOOD			PIERS, OR COLUMNS	
ON SLAB ZONES ZONES		BASE LOOD EVATION	PIERS, OR COLUMNS	
ON SLAB A V ZONES ZONES REFERENCE LEVEL BASE FLOOD ELEVATION REFERENCE ADJACENT			PIERS, OR COLUMNS	
ON SLAB A V ZONES ZONES REFERENCE LEVEL BASE FLOOD ELEVATION REFERENCE ADJACENT			PIERS, OR COLUMNS	
ON SLAB A V ZONES ZONES REFERENCE LEVEL BASE FLOOD ELEVATION REFERENCE ADJACENT			PIERS, OR COLUMNS	

The diagrams above illustrate the points at which the elevations should be measured in A Zones and V Zones.

Elevations for all A Zones should be measured at the top of the reference level floor.

Elevations for all V Zones should be measured at the bottom of the lowest horizontal structural member.